PRODUCT DATA SHEET

Q8 Unishift PC Synt 75W

Synthetic API GL-4 manual transmission fluid

Description

Q8 Unishift PC Synt 75W is a superior manual transmission fluid for passenger cars and light duty vehicles. This versatile lubricant offers exceptional protection and durability, even under extreme pressure, and provides best-in-class thermal stability, making it suitable for a wide variety of passenger car applications. It meets the requirements of most OEMs based on API GL-4.

Applications

Q8 Unishift PC Synt 75W is a versatile lubricant designed to be used in passenger cars and light duty synchromesh manual gearboxes and transaxles, specifically in high load carrying situations. It meets the API GL-4 specification and the requirements of most European and Asian manufacturers.

Benefits

- *Exceptional low temperature fluidity and wide temperature operating range.*
- *Exceptional internal friction reduction.*
- *Excellent easy gear shifting at low temperatures.*
- *Superior protection against wear and extends component life.*
- *Superior protection against rust and corrosion.*

Specifications & Approvals

API	GL-4	**PSA**	B71 2310
Ford	M2C 200-D2	**Toyota**	
Nissan		**VAG**	VW G 052 527

Properties

	Method	Unit	Typical
Density, 15 °C	*D 4052*	*g/ml*	*0,847*
Viscosity Grade	*-*	*-*	*SAE 75W*
Kinematic Viscosity, 40 °C	*D 445*	*mm²/s*	*33*
Kinematic Viscosity, 100 °C	*D 445*	*mm²/s*	*6.8*
Viscosity Index	*D 2270*	*-*	*172*
Brookfield Viscosity, -40 °C	*D 2983*	*Pa.s*	*44*
Pour Point	*D 97*	*°C*	*-39*
Flash Point, P-M	*D 93*	*°C*	*195*

The figures above are not a specification. They are typical figures obtained within production tolerances.