AGRIMAX RT 855 - Technical Specifications



Description	AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.
UM	International Standard
Construction	RADIAL
Machinery	Agriculture: Sprayer, Tractor, Vineyard Harvester

Version	*STANDARD*
Type	*TL*
Tyre Size	*460/85 R 34* *(18.4 R 34)*
LI/SS	*147 A8/B*

Dimensions International Standard

Section Width (mm)	*475*
Overall Diameter (mm)	*1646*
Static Loaded Radius (mm)	*721*
Rolling Circumference (mm)	*4865*
Rim Rec	*W 16 L*
Rim Alt	*W 14 L ; W 15 L*
ECE	*E4-106R-000632*
TRA Code	*R1W*

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1695	1970	2245	2525	2800	3075
40	1695	1970	2245	2525	2800	3075
30	1815	2110	2410	2705	3000	3295
10 LT	2270	2640	3015	3385	3755	4125
10 HT	1815	2110	2410	2705	3000	3295

Printed on 06/06/2021 18:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..