PRODUCT DATA SHEET

Q8 Touring V Long Life 5W-30

Full Synthetic Euro 4, Euro 5 and Euro 6 passenger cars

Description

Q8 Touring V Long LIfe 5W-30 is a synthetic, superior performance passenger car engine oil. This product offers exceptional fuel economy and best-in-class engine protection, especially against wear and sludge, even in the most demanding conditions. It meets ACEA C3 and VW 504.00/507.00.

Applications

Q8 Touring V Long LIfe 5W-30 is suitable for use in Volkswagen diesel and gasoline passenger car, meeting Euro 4, Euro 5 and Euro 6 emission legislation. This superior product is also backwards compatible with most VW gasoline and diesel engines with or without pump injectors.

Benefits

- *Superior protection for exhaust catalyst and diesel particulate filter.*
- *Exceptional engine protection caused by stable viscosity during total service of the oil.*

Specifications, recommendations and approvals

ACEA	C2	**MB**	229.52
ACEA	C3	**Opel/Vauxhall**	OV0401547-G30
API	SP	**Porsche**	C30
BMW	Longlife-04	**VAG**	VW 504.00
GM	Dexos2	**VAG**	VW 507.00

Properties

	Method	Unit	Typical
Density, 15 ˚C	*D 4052*	*g/ml*	*0,852*
Kinematic Viscosity, 40 ˚C	*D 445*	*mm²/s*	*67*
Kinematic Viscosity, 100 ˚C	*D 445*	*mm²/s*	*11.7*
Viscosity Index	*D 2270*	*-*	*172*
Viscosity at high temp. & high shear rate (HTHS)	*CEC-L-36-A-90*	*mPa.s*	*3.7*
Apparent Viscosity, -30 ˚C	*D 5293*	*mPa.s*	*5600*
Pour Point	*D 97*	*˚C*	*-42*
Flash Point, COC	*D 92*	*˚C*	*230*

The figures above are not a specification. They are typical figures obtained within production tolerances.