Tork Mini Jumbo Toilet Roll Advanced

120238



Description

The Tork Mini Jumbo system stands for time efficiency and reduced cost, offering much more toilet paper than standard rolls. Tork Mini Jumbo Toilet Roll Advanced 2 ply balances cost and performance and is suitable for medium to high-traffic locations.

- High capacity: less maintenance and reduced risk of paper shortage
- Attractive décor: designed to make a great impression
- Advanced
- General public use
- Embossing

Certifications

Tork Advanced

Product Details

Embossing	Yes
Print	No
Roll diameter	18.7 cm
Roll length	170 m
Sheet length	20 cm
Ply	2
Roll width	9 cm
Core inside diameter	5.9 cm
System	T2
Color	White

Shipping Data

	Consumer Units (CON)	Transport unit (TRP)	Pallet (PAL)
EAN	7322540489989	7322540489996	7322540948813
Packaging Material	Plastic	-	
Pieces	1	12 (12 CON)	420 (35 TRP)
Height	90 mm	180 mm	1,421 mm
Length	188 mm	561 mm	1,200 mm
Width	188 mm	374 mm	1,000 mm
Gross Weight	247.26 g	6.61 kg	231.25 kg
Net Weight	520.2 g	6.24 kg	218.48 kg
Volume	3.18 dm3	37.77 dm3	1.71 m3
Layers Per Pallet	-	-	7
TRP Per Layer	-	-	5

Tork Mini Jumbo Toilet Roll Advanced

120238

Compatible Products



Tork Mini Jumbo Toilet Roll Disp SS
460006



Tork Mini Jumbo Toilet Roll Disp White
555000



Tork Mini Jumbo Toilet Roll Disp Black
555008



Tork Twin Mini Jumbo TR Disp White
555500

Environmental Information

Content	The product is made from Fresh fibres Recycled fibres Chemicals The packaging material is made from paper or plastic.
Material	Fresh fibres and recycled fibres In the tissue process, both fresh fibres and recovered paper are being used. The choice of pulp is made based on product requirements and pulp availability so the pulp is used in the most efficient way. Recycling of paper is an efficient use of resources as the wood fibres are used more than once. High demands are put on quality and purity of recovered fibres, considering each step of the chain (collection, sorting, transport, storage, use), to ensure safe and hygienic products. Recycled fibres can be produced from different types of recovered paper, such as collected newsprint, magazines, office waste, paper cups, drink cartons, corrugated boxes and paper hand towels. The choice of recovered paper grades is made for each product, depending on its specific requirements on performance properties and brightness. The paper is dissolved in water, washed and treated with chemicals under high temperature and screened to separate out impurities. Fresh fibre pulp is produced from softwood or hardwood. The wood is subject to chemical and /or mechanical processes where the cellulose fibres are separated out and lignin and other residuals are removed.Bleaching of pulp, used for tissue, is primarily a process to remove substances that could have a negative effect on important properties of the finished product such as purity, absorption, strength and colour of the pulp. There are two different methods used today for bleaching fresh fibre pulp: ECF (elementary chlorine free), where chlorine dioxide is used, and TCF (totally chlorine free) where ozone, oxygen and hydrogen peroxide are used. Bleaching of the recycled fibre pulp is done using chlorine-free bleaching agents (hydrogen peroxide and sodium dithionite).
Chemicals	All chemicals (process aids as well as additives) are assessed from an environmental, occupational health and safety and product safety point of view.

Tork Mini Jumbo Toilet Roll Advanced

120238

To control product performance we use additives:

- Wet strength agents (for Wipers and Hand Towels)
- Dry strength agents (are used together with mechanical treatment of the pulp to make strong products like wipers)
- For coloured papers dyes and fixatives (to secure perfect fastness of the colour) are added
- For printed products printing inks (pigments with carriers and fixatives) are applied
- For multi ply products we often use a water soluble glue to secure the integrity of the product

In most of our mills we do not add optical brighteners but it often occurs in recovered paper since it is used in printing paper.

We do not use softeners for professional hygiene products.

High product quality is secured through quality and hygiene management systems throughout production, storage and transport.

In order to maintain a stable process and product quality the paper manufacturing process is supported by the following chemicals/ process aids:

- defoamers (surfactants and dispersing agents)
- pH-control (sodium hydroxide and sulphuric acid)
- retention aids (chemicals that help to agglomerate small fibres to prevent fibre loss)
- Coating chemicals (that help to control the creping of the paper to make it soft and absorbent)

To reuse broke and to utilise recovered fibres we use:

- Pulping aid (chemicals that help to repulp wet strong paper)
- Flocculation chemicals (that help to clean out printing inks and fillers from recovered paper)
- Bleaching agents (to increase the brightness of pulp from recovered paper)

In the cleaning of our waste water we use flocculation agents and nutritients for the biological treatment to secure that no negative impact on water quality comes from our mills.

Environmental certification	This product is certified with the EU Ecolabel with certificate number SE/004/001. This product is certified for FSC® with certificate number SA-COC-008266.
Packaging	Fulfilment of Packaging and Packaging Waste Directive (94/62/EC): Yes
Article creation date and latest article revision	Date of issue: 24-02-2025 Revision date: 17-10-2025
Production	This product is produced at Skelmersdale - GB mill.
Destruction	This product is suitable to be taken care of in the normal sewage system of the community.

Essity UK Ltd, Southfields Road, Dunstable, Bedfordshire LU6 3EJ, United Kingdom